


USG MARS™ HIGH-NRC/HIGH-CAC ACOUSTICAL PANELS


CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER



USG Mars™ High-NRC Acoustical
Panels/USG Donn® Brand DX™/DXL™
Acoustical Suspension System

TO ORDER SAMPLES, GO TO USG.COM OR CGCINC.COM

PREMIUM COLORS



STANDARD COLOR



CUSTOM COLOR



Unlimited
Color Options

FEATURES AND BENEFITS

- Balanced Acoustics. Wide range of options. Sound absorption NRC up to 0.90 and sound attenuation CAC up to 40.
- High light-reflective finish (LR-0.90 White products).
- Washable and scrubbable finish.⁶
- Impact and scratch resistant.⁶
- Coordinates visually with USG Halcyon™ Acoustical Panels for open- or closed-plan applications.
- Nondirectional, monolithic visual reduces installation time and waste.
- ClimaPlus™ 30-year limited system warranty against visible sag, mold and mildew.
- GREENGUARD Gold certified for low emitting performance.

APPLICATIONS

- Offices
- Healthcare
- Classrooms and corridors
- Reception areas and lobbies
- Department stores and retail
- Restaurants and hospitality

SUBSTRATE

- Wet-formed mineral fiber

Fine-Textured Panel

USG MARS™ HIGH-NRC/HIGH-CAC

ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER

ORDER SAMPLES/LITERATURE
USG: samplitt@usg.com
fax: 888 874-2348 | usg.com
CGC: contact Sales Representative

TECHNICAL SERVICES
800 USG.4YOU (874-4968)

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
ULCOM/GG
UL 2818



USG MARS™ HIGH-NRC PANELS 90/30

Plant-Based Binder

USG MARS™ HIGH-NRC PANELS 85/35

Plant-Based Binder

Edge	Panel Size	Fire Rating	Item No.	UL Classified ⁵			Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
				NRC	CAC Min.	LR ²						
SQ	2'x2'x1"	Class A	88137	0.90	30	0.90	White, color ⁷	A,B,C	Low		67%	\$\$\$
	2'x4'x1"	Class A	89137	0.90	30	0.90	White	A,B	Low		67%	\$\$\$
	30"x30"x1"	Class A	80213	0.90	30	0.90	White	A,B	Low		67%	\$\$\$
	30"x60"x1"	Class A	89143	0.90	30	0.90	White	A,B	Low		67%	\$\$\$
SLT	2'x2'x1"	Class A	88138	0.90	30	0.90	White, color ⁷	D	Low		67%	\$\$\$
	2'x4'x1"	Class A	89138	0.90	30	0.90	White	D	Low		67%	\$\$\$
	30"x30"x1"	Class A	80239	0.90	30	0.90	White	D	Low		67%	\$\$\$
	30"x60"x1"	Class A	89144	0.90	30	0.90	White	D	Low		67%	\$\$\$
FLB	2'x2'x1"	Class A	88139	0.90	30	0.90	White, color ⁷	E,F,G,H	Low		67%	\$\$\$
	2'x4'x1"	Class A	89139	0.90	30	0.90	White	E,F,G,H	Low		67%	\$\$\$
	30"x30"x1"	Class A	80265	0.90	30	0.90	White	E,F,G,H	Low		67%	\$\$\$
	30"x60"x1"	Class A	89145	0.90	30	0.90	White	E,F,G,H	Low		67%	\$\$\$
SQ	2'x2'x7/8"	Class A	88134	0.85	35	0.90	White, color ⁷	A,B,C	Low		68%	\$\$\$
	2'x4'x7/8"	Class A	89134	0.85	35	0.90	White	A,B	Low		68%	\$\$\$
	30"x30"x7/8"	Class A	80113	0.85	35	0.90	White	A,B	Low		68%	\$\$\$
	30"x60"x7/8"	Class A	89140	0.85	35	0.90	White	A,B	Low		68%	\$\$\$
SLT	2'x2'x7/8"	Class A	88135	0.85	35	0.90	White, color ⁷	D	Low		68%	\$\$\$
	2'x4'x7/8"	Class A	89135	0.85	35	0.90	White	D	Low		68%	\$\$\$
	30"x30"x7/8"	Class A	80139	0.85	35	0.90	White	D	Low		68%	\$\$\$
	30"x60"x7/8"	Class A	89141	0.85	30	0.90	White	D	Low		68%	\$\$\$
FLB	2'x2'x7/8"	Class A	88136	0.85	35	0.90	White, color ⁷	E,F,G,H	Low		68%	\$\$\$
	2'x4'x7/8"	Class A	89136	0.85	35	0.90	White	E,F,G,H	Low		68%	\$\$\$
	30"x30"x7/8"	Class A	80165	0.85	35	0.90	White	E,F,G,H	Low		68%	\$\$\$
	30"x60"x7/8"	Class A	89142	0.85	35	0.90	White	E,F,G,H	Low		68%	\$\$\$

Low Emissions (VOC)

Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.1 - 2010 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.com and at productguide.ulenvironment.com.

ClimaPlus™ Warranty Performance³

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content

Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

USG MARS™ HIGH-NRC/HIGH-CAC

ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER


ORDER SAMPLES/LITERATURE
 USG: samplit@usg.com
 fax: 888.874.2348 | usg.com
 CGC: contact@salesrepresentative.com

TECHNICAL SERVICES
 800 USG.4YOU (874-4968)

FOR MOST UP-TO-DATE TECHNICAL INFORMATION AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com



PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS:
 UL/COM/GG
 UL 2818



USG MARS™ HIGH-NRC/HIGH-CAC PANELS 80/40

Plant-Based Binder

USG MARS™ HIGH-NRC PANELS 80/35

Plant-Based Binder

USG MARS™ HIGH-CAC PANELS 60/40

Edge	Panel Size	Fire Rating	Item No.	UL Classified			Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content¹	Panel Cost
				NRC	CAC Min.	LR²						
	2'x2'x1"	Class A	86345	0.80	40	0.90	White	A,B,C	Low		69%	\$
	2'x4'x1"	Class A	88345	0.80	40	0.90	White	A,B	Low		69%	\$
	2'x2'x1"	Class A	86346	0.80	40	0.90	White	D	Low		69%	\$
	2'x4'x1"	Class A	88346	0.80	40	0.90	White	D	Low		69%	\$
	2'x2'x1"	Class A	86347	0.80	40	0.90	White	E,F,G,H	Low		69%	\$
	2'x4'x1"	Class A	88347	0.80	40	0.90	White	E,F,G,H	Low		69%	\$
	2'x2'x7/8"	Class A	86100	0.80	35	0.90	White	A,B,C	Low		69%	\$
	2'x4'x7/8"	Class A	86300	0.80	35	0.90	White	A,B	Low		69%	\$
	30"x30"x7/8"	Class A	86426	0.80	35	0.90	White	A,B	Low		69%	\$
	30"x60"x7/8"	Class A	86429	0.80	35	0.90	White	A,B	Low		69%	\$
	2'x2'x7/8"	Class A	87200	0.80	35	0.90	White	D	Low		69%	\$
	2'x4'x7/8"	Class A	89600	0.80	35	0.90	White	D	Low		69%	\$
	30"x30"x7/8"	Class A	86500	0.80	35	0.90	White	D	Low		69%	\$
	30"x60"x7/8"	Class A	86466	0.80	35	0.90	White	D	Low		69%	\$
	2'x2'x7/8"	Class A	87100	0.80	35	0.90	White	E,F,G,H	Low		69%	\$
	2'x4'x7/8"	Class A	89500	0.80	35	0.90	White	E,F,G,H	Low		69%	\$
	30"x30"x7/8"	Class A	86400	0.80	35	0.90	White	E,F,G,H	Low		69%	\$
	30"x60"x7/8"	Class A	86497	0.80	35	0.90	White	E,F,G,H	Low		69%	\$
	2'x2'x3/4"	Class A	86186	0.60	40	0.90	White, color⁷	A,B,C	Low		79%	\$\$\$
	2'x4'x3/4"	Class A	87187	0.60	40	0.90	White	A,B	Low		79%	\$\$\$
	2'x2'x3/4"	Class A	86786	0.60	40	0.90	White, color⁷	D	Low		79%	\$\$\$
	2'x4'x3/4"	Class A	88786	0.60	40	0.90	White	D	Low		79%	\$\$\$
	2'x2'x3/4"	Class A	86986	0.60	40	0.90	White, color⁷	E,F,G,H	Low		79%	\$\$\$
	2'x4'x3/4"	Class A	88986	0.60	40	0.90	White	E,F,G,H	Low		79%	\$\$\$

Low Emissions (VOC)

Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.1 - 2010 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.com and at productguide.ulenvironment.com.

ClimaPlus™ Warranty Performance³

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content

Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
ULCOM/GG
UL 2818

GRID PROFILE OPTIONS

PHYSICAL DATA/ FOOTNOTES

USG MARS™ HIGH-NRC/HIGH-CAC ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER



Declare.

ORDER SAMPLES/LITERATURE
USG: samplitt@usg.com
fax: 888 874-2348 | usg.com
CGC: contact Sales Representative

TECHNICAL SERVICES
800 USG.4YOU (874-4968)

**FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL**
usgdesignstudio.com
cgcdesignstudio.com

A USG DX"/DXL™	B USG DXW™	C ⁴ USG Centricitee™ DXT™	D USG DX"/DXL™	E USG Centricitee™ DXT™	F USG Fineline® DXF™	G ⁸ USG Fineline® 1/8 DXFF™	H USG Identitee® DXI™

Product literature
Data sheet: SC2487

ASTM E1264 classification
Type IV, Form 1 and 2, Pattern E, G

**ASTM E84 and CAN/ULC S102
surface-burning characteristics**
Class A
Flame spread: 25 or less
Smoke developed: 50 or less

Weight
1.05-1.26 lb./sq. ft.

Online tools
usgdesignstudio.com or cgcdesignstudio.com

Thermal resistance
R-2.2

Maximum backloading
See *USG 30-Year Limited System Warranty
Commercial Applications* (SC2102).

Maintenance
Can be cleaned easily with a soft brush or vacuum. To clean white panels, use a clean, white cloth with water or a mild detergent and wipe surface.

Metric sizes available
Contact sales for minimum quantities and lead times.

Notes

1. For details, see LEED report tool at usgdesignstudio.com or cgcdesignstudio.com.
2. LR values are shown as averages.
3. Panel face and back surfaces treated with a proprietary, broad-spectrum antimicrobial additive that inhibits and retards the growth of mold, mildew and bacteria. For details, see *USG 30-Year Limited System Warranty Commercial Applications* (SC2102) and *Ceilings Certification of Performance* (SC2451).
4. Maximum 2'x2' with SQ edge panels.
5. Acoustic values are for white only. Colored values are lower depending on specific color selected.
6. White panels only.
7. Available in Premium and Custom Colors.
8. Not available in Premium or Custom Colors.

Notice

The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

SC2487/rev. 10-18
© 2018 USG Corporation and/or its affiliates. All rights reserved. Printed in USA

Manufactured by
USG Interiors, LLC
550 West Adams Street
Chicago, IL 60661

The trademarks USG, CGC, CENTRICITEE, CLIMAPLUS, DONN, DX, DXF, DXFF, DXI, DXL, DXT, DXW, FINELINE, HALCYON, IDENTITEE, MARS, IT'S YOUR WORLD. BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

