

USG OLYMPIA™ MICRO™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

USG Olympia™ Micro™ Acoustical
Panels with ClimaPlus™ Performance/
USG Donn® Brand Finline® DXF™
Acoustical Suspension System

TO ORDER SAMPLES, GO TO USG.COM OR CGCINC.COM



Flat White
050

Fine-Textured Panel

FEATURES AND BENEFITS

- Nondirectional pattern reduces installation time and waste.
- Economical, fine-textured panel.
- Excellent light-reflective finish (LR-0.86) reduces light fixtures and energy use.
- Available in Optimized Recycled Content formulations to help maximize LEED recycled content contribution.
- USDA Certified Biobased Product.⁷
- ClimaPlus™ 30-year limited system warranty against visible sag, mold and mildew.

APPLICATIONS

- Offices
- Classrooms
- Reception/lobby areas
- Hotels
- Conference areas
- Retail stores

SUBSTRATE

- Wet-formed mineral fiber

USG OLYMPIA™ MICRO™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

ORDER SAMPLES/LITERATURE
 USG: samplitt@usg.com
 fax: 888.874.2348 | usg.com
CGC: contact Sales Representative

TECHNICAL SERVICES
 800.USG.4YOU (874-4968)

**FOR MOST UP-TO-DATE
 TECHNICAL INFORMATION
 AND LEED REPORT TOOL**
usgdesignstudio.com
cgcdesignstudio.com



PRODUCT CERTIFIED
 FOR LOW CHEMICAL
 EMISSIONS:
 UL COM/GG
 UL 2818

30 YEAR LIMITED SYSTEM
 WARRANTY
 • No Visible Sag
 • Mold/Mildew Protection

10 YEAR
 AVAILABILITY
 4211, 4221, 4231,
 4411, 4421, 4742,
 4744

HRC HIGH RECYCLED
 CONTENT



USG OLYMPIA™ MICRO™ PANELS UNPERFORATED

USG OLYMPIA™ MICRO™ PANELS 50 NRC⁶

USG OLYMPIA™ MICRO™ PANELS 60 NRC⁶

USG OLYMPIA™ MICRO™ ILLUSION™ TWO/24 PANELS

PATTERNS

UL Classified												
Edge	Panel Size	Fire Rating	Item No.	NRC	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew	Recycled Content ¹	Panel Cost
	2'x2'x5/8"	Class A	4210	—	35	0.86	White	A,B,C	Low		44%	\$
	2'x4'x5/8"	Class A	4913	—	35	0.86	White	A,B	Low		44%	\$
	2'x2'x5/8"	Class A	4211	0.50	30	0.86	White	A,B,C	Low		44%	\$
	2'x4'x5/8"	Class A	4411	0.50	30	0.86	White	A,B	Low		44%	\$
	2'x4'x5/8"	Class A	4411HRC	0.50	30	0.86	White	A,B	Low		53%	\$
	2'x2'x5/8"	Class A	4221	0.50	35	0.86	White	D	Low		44%	\$
	2'x2'x5/8"	Class A	4221HRC	0.50	35	0.86	White	D	Low		53%	\$
	2'x4'x5/8"	Class A	4421	0.50	35	0.86	White	D	Low		44%	\$
	2'x4'x5/8"	Class A	4421HRC	0.50	35	0.86	White	D	Low		53%	\$
	2'x2'x5/8"	Class A	4231	0.50	35	0.86	White	E,F,G,H	Low		44%	\$
	2'x2'x5/8"	Class A	4231HRC	0.50	35	0.86	White	E,F,G,H	Low		53%	\$
	2'x4'x5/8"	Class A	4431	0.50	35	0.86	White	E,F,G,H	Low		44%	\$
	2'x2'x3/4"	Class A	4750	0.60	33	0.86	White	A,B,C	Low		61%	\$
	2'x4'x3/4"	Class A	4751	0.60	33	0.86	White	A,B	Low		61%	\$
	2'x2'x3/4"	Class A	4752	0.60	35	0.86	White	D	Low		61%	\$
	2'x4'x3/4"	Class A	4753	0.60	35	0.86	White	D	Low		61%	\$
	2'x2'x3/4"	Class A	4754	0.60	35	0.86	White	E,F,G,H	Low		61%	\$
	2'x4'x3/4"	Class A	4755	0.60	35	0.86	White	E,F,G,H	Low		61%	\$
	2'x4'x3/4"	Class A	4742	0.50	35	0.86	White	D	Low		61%	\$
	2'x4'x3/4"	Class A	4744	0.50	35	0.86	White	I,J	Low		61%	\$

USG Illusion™ Two/24



The look of 2'x2' panels

Low Emissions (VOC)

Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.1 - 2010 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.com and at productguide.ulenvironment.com.

ClimaPlus™ Warranty Performance³

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content

Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

GRID PROFILE OPTIONS

A USG DX"/DXL™	B USG DXW™	C ⁷ USG Centricitee™ DXT™	D USG DX"/DXL™	E USG Centricitee™ DXT™	F USG Identitee® DXI™	G USG Fineline® DXF™	H USG Fineline® 1/8 DXFF™	I USG Centricitee™ DXT™	J USG Identitee® DXI™

PHYSICAL DATA/ FOOTNOTES

Notice

The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

SC2180/rev. 11-16

© 2016 USG Corporation and/or its affiliates. All rights reserved. Printed in U.S.A.

Product literature
 Data sheet: SC2180

ASTM E1264 classification
 Type III, Form 2, Pattern CE

ASTM E84 and CAN/ULC S102
 surface-burning characteristics

Class A
 Flame spread: 25 or less
 Smoke developed: 50 or less

Online tools
usgdesignstudio.com or cgcdesignstudio.com

Weight
 0.78–1.03 lb./sq. ft.

Thermal resistance
 R-1.4 (5/8" panels)
 R-1.7 (3/4" panels)

Maximum backloading
 See USG 30-Year Limited System Warranty Commercial Applications (SC2102).

Maintenance
 Can be cleaned easily with a soft brush or vacuum.

Notes

- For details, see LEED report tool at usgdesignstudio.com or cgcdesignstudio.com.
- LR values are shown as averages.
- For details, see USG 30-Year Limited System Warranty Commercial Applications (SC2102) and ClimaPlus™ Ceilings Certification of Performance (SC2451).
- Panels have 15/16" routing.
- Panels have 9/16" routing.

6. Mixing 0.50 and 0.60 NRC panels in the same ceiling plane is not recommended.

7. This product has achieved both BioPreferred initiatives: Federal Procurement Preference and Certified Product Labeling. See the complete listing of all USG ceiling panels on biopreferred.gov website.

Manufactured by
 USG Interiors, LLC
 550 West Adams Street
 Chicago, IL 60661

The trademarks USG, CGC, CENTRICITEE, CLIMAPLUS, DONN, DX, DXF, DXFF, DXI, DXL, DXT, DXW, FINELINE, IDENTITEE, ILLUSION, MICRO, OLYMPIA, IT'S YOUR WORLD. BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

